

2025

Z900 SE ABS

Kawasaki
Let the Good Times Roll®



METALLIC MATTE GRAPHITE GRAY/EBONY/
METALLIC GRAPHITE GRAY



POTENCIA

| | |
|---------------------------------------|--|
| Motor | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled |
| Cilindrada | 948cc |
| Diámetro por carrera | 73.4 x 56.0mm |
| Relación de compresión | 11.8:1 |
| Potencia máxima | 123.0 hp ¹ @ 9,500 rpm |
| Par motor máximo | 73.1 lb-ft @ 7,700 rpm |
| Sistema de combustible | DFI® with 36mm throttle bodies |
| Encendido | TCBI with Electronic Advance |
| Transmisión | 6-speed, return shift |
| Transmisión final | Sealed chain |
| Asistencia electrónica para el piloto | Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness |

RENDIMIENTO

| | |
|--|--|
| Suspensión delantera/recorrido del neumático | 41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in |
| Suspensión trasera/recorrido del neumático | Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in |
| Neumático delantero | 120/70-17 |

| | |
|-------------------|--|
| Neumático trasero | 180/55-17 |
| Frenos delanteros | Dual 300mm semi-floating discs with radial-mount 4-piston Brembo M4.32 monobloc calipers and ABS |
| Frenos traseros | Single 250mm disc with single-piston caliper and ABS |

DETALLES

| | |
|----------------------------|---|
| Tipo de chasis | Trellis, high tensile steel |
| Ángulo de dirección/Avance | 24.7° / 4.3 in |
| Largo total | 81.3 in |
| Ancho total | 32.7 in |
| Altura del asiento | 44.7 in |
| Distancia al suelo | 5.7 in |
| Altura del asiento | 31.9 in |
| Peso seco estimado | 425.6 lb** / 427.8 lb** 50-State Model |
| Peso en orden de marcha | 469.7 lb* / 471.9 lb* 50-State Model |
| Depósito de combustible | 4.5 gal |
| Distancia entre ejes | 57.1 in |
| Características especiales | 5" All-digital TFT color instrumentation, All-LED lighting, USB Type-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLGY THE APP MOTORCYCLE*** |
| Colores disponibles | Metallic Matte Graphite Gray/Ebony/Metallic Graphite Gray |
| Garantía | 12 Month Limited Warranty |

Escanear con
cámara para ver
videos, característi-
cas clave y más.



¹Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
²Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
³RIDEOLGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
⁴This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite mexico.kawasaki-la.com para obtener detalles completos del producto.