
NINJA® 1100SX ABS









POTENCIA

Motor 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Cilindrada 1,099cc

Diámetro por carrera 77.0 x 59.0mm

Relación de compresión 11.8:1

Potencia máxima 134.0 hp1 @ 9,000 rpm

Par motor máximo 83.2 lb-ft @ 7,600 rpm

Sistema de combustible DFI® with 38mm Electronic Throttle Valves

Encendido TCBI with Digital Advance

Transmisión 6-speed, return shift with wet multi-disc manual Assist &

Slipper Clutch

Transmisión final Sealed chain

Asistencia

electrónica para el piloto

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent antilock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

RENDIMIENTO

Suspensión delantera/recorrido del neumático

Suspensión trasera/ recorrido del neumático

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

Horizontal back-link, gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in

Neumático delantero 120/70-17 Neumático trasero 190/50-17

Frenos delanteros Dual 300mm discs with radial-mount 4-piston monobloc

calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Single 260mm disc with single-piston caliper, Kawasaki Frenos traseros

Intelligent anti-lock Brake System (KIBS)

DETALLES

Tipo de chasis Twin-spar aluminum

Ángulo de dirección/ 24.0°/3.9 in **Avance**

Largo total 82.7 in **Ancho total** 31.7 in

Altura del asiento 46.9 in/48.2 in w/ windshield high

Distancia al suelo 5.3 in Altura del asiento 32.3 in Peso seco estimado 471.9 lb** Peso en orden de 518.2 lb*

Depósito de 5.0 gal combustible

marcha

Specifications subject to change. Visite mexico.kawasaki-la.com para obtener detalles completos del producto.

Distancia entre ejes

Características 4.3" All-digital TFT Instrumentation, All-LED lighting, USB especiales Type-C outlet, Smartphone Connectivity with available Voice Command via RIDEOLOGY THE APP MOTORCYCLE***

Metallic Brilliant Golden Black/Metallic Carbon Gray **Colores disponibles**

Escanear con cámara para ver videos, características clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). *RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.